

DS-TVL224-8-5EY

Outdoor LED Display for Speed Information



Outdoor LED Display for Speed Information
DS-TVL224-8-5EY, placed in the enclosed area, industrial park, enterprise park, campus, port, etc., displays the information of speed and license plate. It can display red, green, and yellow to represent different speed status.

Meanwhile, the display content keeps flashing when it reports the over speeding, which reminds the driver to pay attention to the illegal behavior. What's more, it integrates with highlight LED lamp beads, which are visible within 50 meters. The display also features in lightweight, easy mounting, and anti-corrosion shell. It can apply to various scenarios.

- Placed in the enclosed area, industrial park, enterprise park, campus, port, etc., displaying the information of speed and license plate.
- Displays three colors to represent different speed status, such as over speed, normal speed, etc., to remind drivers of the illegal driving behavior.
- Max. visible distance is up to 50 m, making drivers notice the information in time.
- The communication interface is RJ45/RS-485, making connection more convenient.
- Supports various environments with the working temperature range of -30 °C to 60 °C.





Specification


Specification	
Display for Speed	
Character Standard	Number 8
Character Number	2
Color	Red, Green, Yellow
Size	Width: 641 mm, Height: 540 mm (approximately)
Display for License Plate	
Character Standard	P10
Color	Red, Green, Yellow
Size	Width: 641 mm, height: 161 mm
Resolution	64 × 16
Display	
LED	DIP346
Pixel Composition	Display for speed: 1R1G, display for license plate: 2R1G
Luminance	5,000 cd/m ²
Viewing Angle	Horizontal: 110°/ Vertical: 60°
Max. Visual Range	50 m
Module Interface	HUB12
Power Supply	100 to 240 VAC, 50/60 Hz
LED Lifetime	100,000 hours
Max. Power Consumption	200 W
Average Power Consumption	80 W
Temperature	-30 ºC to 60 ºC
Humidity	10% to 95%
Materials	Aluminum plate
Dimension	Width: 740 mm, Height: 850 mm, Depth: 90 mm
Weight	25 kg
Protection	IP54

Available Model

DS-TVL224-8-5EY



Typical Application




Product Showcase

Various Color Display





Flexible Configuration Different Colors Represent Different Speed Ranges







Dimension














Distributed by

HIKVISION°

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA

T+1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T +61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T +662-275-9949 sales.thailand@hikvision.com Hikvision Europe T +31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T +39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33[0]1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T+7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T+7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-[0]31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T+62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com