

DS-MH2311 Series Body Camera

Introduction

DS-MH2311 Series Body camera, a video recording system, is typically used by law enforcement officers to record their interactions with the public and gather video evidences at crime scenes.





Key Features

- H.264 and H.265 encoding technology.
- Up to 1080p/30 fps recording resolution.
- Wide-range lens with 160° diagonal FOV.
- Dismountable battery design.
- Built-in GPS module.
- 3G/4G network transmission.
- 2.4 inch TFT LCD.
- Light weight (190 g without shoulder clip).
- Small size $(95 \times 60 \times 29 \text{ mm})$
- IP67, IK10.

Available Models

DS-MH2311/128G, DS-MH2311/128G/GLE





Specifications


Model		DS-MH2311/128G	DS-MH2311/128G/GLE	
Sensor	Туре	1/3" CMOS		
Sensor	FOV	diagonal FOV: 160° (wide tele)		
Display	Dimensions	2.4" TFT LCD		
Video Parameters	Video Input	1080p		
	Video Resolution	1080p/60fps, 720p/120fps, 704*480		
	Main Stream	1080p/30 fps		
	Sub-stream	720p/30 fps		
	Codec	H.264 and H.265 codec.		
	Video Format	.mp4		
	OSD	Time / date / ID / GPS coordinates		
	Audio input	A built-in 2 internal microphone.		
	Picture Resolution	Up to 16 MP		
	Picture Format	.jpg		
	Playback speed	1/16x,1/8x,1/4x,1/2x,1x,2x,4x,8x,16x,32x, 64x		
	Shutter	Digital shutter		
	Day & Night	IR cut filter with auto switch		
	White Balance	Auto		
	Flashing Light	Supported (up to 10 m)		
	IR Light	Supported (up to 10 m)		
	Smart IR	Supported		
	Laser Positioning	Supported		
	API	Open API (Russian language)		
	Sensors	G-Sensor, Light Sensor, Temperature Sensor.		
	VCA Face detection	Supported		
	language English, Russian, Chinese			
Storage	Capacity	128G TF card	A built-in EMMC storage chip of 128 GB capacity	
	Record on startup	Auto / manual	Auto / manual	
	Record time	Up to 30 min	Up to 30 min	
	Lock cycle record	Supported	Supported	
	Snapshot	No video interruption up to 2pcs/sec	No video interruption up to 2pcs/sec	
Positioning	Satellite Positioning	Built-in GPS module (GPS/GLONASS)		
Network Transmission	4G	Not supported	Frequency band: FDD LTE: Band 1, Band 2, Band 3, Band 4, Band 5, Band 7, Band 8, Band 20 WCDMA/HSDPA/HSUPA/HSPA+: Band 1, Band 2, Band 5, Band 8 GSM/GPRS/EDGE: 850 MHz/900 MHz/1800 MHz/1900 MHz	
	Wi-Fi	802.11b/g/n	, , , , , , , , , , , , , , , , , , , ,	





	Remote connection	Support with transmition video, audio and GPS coordinates from central monitoring system.	
General	Working Temperature	-25 °C to +60 °C (-4 °F to +131 °F)	
	Working Humidity	≤ 90%	
	Ingress Protection Level	IP67, IK10, protection from falling from a height of 2m	
	Material	Metal and plastic	
	Dimensions (L × W × H)	95 × 60 × 29 mm (3.7 × 2.4 × 1.1 inch)	
	Weight	Body camera: 190 g (without should clip) (0.4 lb) With package: 515 g (1.1 lb)	
	Buttons	Power switch, Recording button, taping button, capture button, two-way audio button, attention sos button, menu button, up button, down button, OK button, PTT button.	
Others	USB Interface	Mini USB 2.0	
	Charging	Charging via USB interface/dock station	
	Battery	A dismountable battery with 3,300 mAh capacity which can record videos up to 8 hours and can connect external battery.	
	Charging time	Up to 4 hours	
	Charge cycle	Up to 700 cycle	
	Status device	sound signals about the state of the device	




Dimensions














Distributed by

HIKVISION°

Headquarters

No.555 Qianmo Road, Binjiang District, Hangzhou 310051, China T +86-571-8807-5998 overseasbusiness@hikvision.com

Hikvision USA

T+1-909-895-0400 sales.usa@hikvision.com

Hikvision Australia T+61-2-8599-4233 salesau@hikvision.com

Hikvision India T+91-22-28469900 sales@pramahikvision.com

Hikvision Canada T+1-866-200-6690 sales.canada@hikvision.com

Hikvision Thailand T+662-275-9949 sales.thailand@hikvision.com Hikvision Europe

T+31-23-5542770 sales.eu@hikvision.com

Hikvision Italy T+39-0438-6902 info.it@hikvision.com

Hikvision Brazil T +55 11 3318-0050 Latam.support@hikvision.com

Hikvision Turkey T +90 (216)521 7070- 7074 sales.tr@hikvision.com

Hikvision Malaysia T+601-7652-2413 sales.my@hikvision.com Hikvision UK & Ireland T +01628-902140 sales.uk@hikvision.com

Hikvision South Africa Tel: +27 (10) 0351172 sale.africa@hikvision.com

Hikvision France T +33[0]1-85-330-450 info.fr@hikvision.com

Hikvision Kazakhstan T +7-727-9730667 nikia.panfilov@hikvision.ru

Hikvision Vietnam T +84-974270888 sales.vt@hikvision.com Hikvision UAE T +971-4-4432090 salesme@hikvision.com

Hikvision Singapore T +65-6684-4718 sg@hikvision.com

Hikvision Spain T +34-91-737-16-55 info.es@hikvision.com

Hikvision Tashkent T +99-87-1238-9438 uzb@hikvision.ru

Hikvision Hong Kong T +852-2151-1761 info.hk@hikvision.com Hikvision Russia T+7-495-669-67-99 saleru@hikvision.com

Hikvision Korea T +82-[0]31-731-8817 sales.korea@hikvision.com

Hikvision Poland T +48-22-460-01-50 info.pl@hikvision.com

Hikvision Indonesia T +62-21-2933759 Sales.Indonesia@hikvision.com

Hikvision Colombia sales.colombia@hikvision.com