

## DS-WSEWI-T2/4200 Workstation



### Introduction

Embedded with Windows 10 operating system and iVMS-4200 client software, the DS-WSEWI-T2/4200 Workstation is a cost-effective VMS product.

You can achieve central configuration and management of all Hikvision video, access control, and intercom products. With accelerated hardware decoding technology, you can easily live view and playback up to 15-ch @1080p.

DS-WSEWI-T2/4200 is a professional video surveillance management product, it is widely used in small to middle scale chain management.

### Key Feature

- Pre-installed iVMS-4200 and Windows 10 IoT Enterprise OS
- Enterprise-class SSD for fast system boot and daily running
- Overall management of video, access control, alarm, and intercom
- Accelerated video decoding based on GPU
- 2 HDMI (up to 4K) and 1 VGA output
- Support 24/7 working

### Typical Application




## Specifications

Model		DS-WSEWI-T2/4200
System	Processor	Intel® Celeron® Processor J3455 (2M Cache, up to 2.3 GHz), 64 bit, 4 Core;
	Memory	DDR3L, 4GB
	Graphics card	Intel® HD Graphics 500
	Operating system	Win10 IoT Ent LTSB 2016 Entry EPKEA, 64 bit
Storage	System disk (OS, VMS)	mSATA 64GB
		<b>Optional:</b> mSATA 128GB
Storage	SATA interface	2, SATA interface <sup>1</sup>
		1TB/2TB/3TB/4TB/5TB/6TB/8TB/10TB capacity for each disk
Decoding	Decoding capacity	15-ch @1080p (with video recording function disabled)
Video/Audio output	HDMI interface	2, HDMI interface
		4K (3840 × 2160), 2K (2560 × 1600), 1920 × 1080, 1680 × 1050, 1600 × 900, 1440 × 900, 1280 × 1024, 1280 × 960, 1024 × 768, 800 × 600
	VGA interface	1 × VGA interface
		1920 × 1080, 1680 × 1050, 1600 × 900, 1440 × 900, 1280 × 1024, 1280 × 960, 1024 × 768, 800 × 600
	Audio input	1-ch, 3.5 mm line in connector
Audio output	1-ch, 3.5 mm line out connector	
External interface	LAN	2 × RJ45 10M/100M/1000M self-adaptive Ethernet interface
	USB interface	Front panel: 2 × USB 2.0; Rear panel: 2 × USB 3.0
	Serial interface	1 RS-232
iVMS-4200	Screen division	Support up to 64 screen split
	Synchronous playback	Support up to 16-ch synchronous playback
	Person	Support up to 10,000 persons Support up to 5 cards for each person
	Access control device	Support up to 16 access control devices
	Access control point	Support up to 64 access control points
General	Power supply	12 VDC
	Consumption (without hard disk)	≤ 30 W
	Working temperature	0° C to 45° C (32° F to 113° F)
	Working humidity	10% to 90% (Non-condensing)
	Chassis	19-inch rack-mounted 1U chassis
	Dimensions (W × D × H)	440 × 260 × 48 mm (17.3" × 10.2" × 1.9")
Weight (without hard disk)	≤ 4 kg (8.8 lb)	

1: It is not recommended to install or use the iVMS-4200 video recording function.

If you require to store recording video on the local device during live view or playback, please install one or two hard disks.

## Physical Interfaces



Index	Description	Index	Description
1	AUDIO IN/OUT	6	12 VDC Power Supply
2	VGA Output Interface	7	GND
3	HDMI1 and HDMI2 Interfaces	8	Power Switch
4	USB 3.0 Interfaces	9	RS-232 Serial Interface
5	LAN1 and LAN2 Interfaces		

## Available Models

DS-WSEWI-T2/4200

Distributed by



### Headquarters

No.555 Qianmo Road, Binjiang District,  
Hangzhou 310051, China  
T +86-571-8807-5998  
overseasbusiness@hikvision.com

**Hikvision USA**  
T +1-909-895-0400  
sales.usa@hikvision.com

**Hikvision Australia**  
T +61-2-8599-4233  
salesau@hikvision.com

**Hikvision India**  
T +91-22-28469900  
sales@pramahikvision.com

**Hikvision Canada**  
T +1-866-200-6690  
sales.canada@hikvision.com

**Hikvision Thailand**  
T +662-275-9949  
sales.thailand@hikvision.com

**Hikvision Europe**  
T +31-23-5542770  
sales.eu@hikvision.com

**Hikvision Italy**  
T +39-0438-6902  
info.it@hikvision.com

**Hikvision Brazil**  
T +55 11 3318-0050  
Latam.support@hikvision.com

**Hikvision Turkey**  
T +90 (216)521 7070- 7074  
sales.tr@hikvision.com

**Hikvision Malaysia**  
T +601-7652-2413  
sales.my@hikvision.com

**Hikvision UK & Ireland**  
T +01628-902140  
sales.uk@hikvision.com

**Hikvision South Africa**  
Tel: +27 (10) 0351172  
sale.africa@hikvision.com

**Hikvision France**  
T +33(0)1-85-330-450  
info.fr@hikvision.com

**Hikvision Kazakhstan**  
T +7-727-9730667  
nikia.panfilov@hikvision.ru

**Hikvision Vietnam**  
T +84-974270888  
sales.vt@hikvision.com

**Hikvision UAE**  
T +971-4-4432090  
salesme@hikvision.com

**Hikvision Singapore**  
T +65-6684-4718  
sg@hikvision.com

**Hikvision Spain**  
T +34-91-737-16-55  
info.es@hikvision.com

**Hikvision Tashkent**  
T +99-87-1238-9438  
uzb@hikvision.ru

**Hikvision Hong Kong**  
T +852-2151-1761  
info.hk@hikvision.com

**Hikvision Russia**  
T +7-495-669-67-99  
saleru@hikvision.com

**Hikvision Korea**  
T +82-(0)31-731-8817  
sales.korea@hikvision.com

**Hikvision Poland**  
T +48-22-460-01-50  
info.pl@hikvision.com

**Hikvision Indonesia**  
T +62-21-2933759  
Sales.Indonesia@hikvision.com

**Hikvision Colombia**  
sales.colombia@hikvision.com