## TVS-472XT-PT-4G

| | |
|---|---|
| CPU | Intel® Pentium G5400T 2-core 3.1 GHz Processor |
| CPU Architecture | 64-bit x86 |
| Graphic Processors | Intel® UHD Graphics 610 |
| Floating Point Unit | Yes |
| Encryption Engine | Yes (AES-NI) |
| Hardware-accelerated Transcoding | Yes |
| System Memory | 4 GB SODIMM DDR4 (2 x 2 GB) |
| Maximum Memory | 32 GB ( 2 x 16 GB) |
| Memory Slot | 2 x SO-DIMM DDR4 |
| Flash Memory | 4GB (Dual boot OS protection) |
| Drive Bay | 4 x 3.5-inch |
| Drive Compatibility | 3.5-inch bays:<br>3.5-inch SATA hard disk drives<br>2.5-inch SATA hard disk drives<br>2.5-inch SATA solid state drives |
| Hot-swappable | Yes |
| M.2 SSD Slot | 2 x M.2 2280 PCIe Gen3 x2 slots |
| SSD Cache Acceleration Support | Yes |
| Gigabit Ethernet Port (RJ45) | 2 |
| 10 Gigabit Ethernet Port | 1 x 10GBASE-T (10G/5G/2.5G/1G/100M) |
| Jumbo Frame | Yes |
| Thunderbolt Port | 2 |
| PCIe Slot | 2<br>Slot 1: PCIe Gen3 x16 (CPU)<br>Slot 2: PCIe Gen3 x4 (PCH) |
| USB 3.0 port | 1 |
| USB 3.1 Gen 2 (10Gbps) Port | 2 x Type-C USB 3.1 Gen2 5V/3A 10Gbps<br>2 x Type-A USB 3.1 Gen2 5V/1A 10Gbps |
| IR Sensor | Yes (QNAP RM-IR004 & MCE) |
| HDMI Output | 1, HDMI 2.0 (up to 3840 x 2160 @ 60Hz) |
| Audio Input | 1 x 3.5mm microphone input jacks |
| Audio Output | speaker, 3.5mm line out jack |

| | |
|---|---|
| Form Factor | Tower |
| LED Indicators | HDD 1-4, Status, LAN, USB port, M.2 port |
| LCD Display/ Button | Yes |
| Buttons | Power, Reset, USB Copy |
| Dimensions (HxWxD) | 188.2, 199.3, 279.6 |
| Weight (Net) | 5.4 |
| Weight (Gross) | 7.01 |
| Operating temperature | 0 - 40 °C (32°F - 104°F) |
| Relative Humidity | 5-95% RH non-condensing, wet bulb: 27˚C (80.6˚F) |
| Power Supply Unit | 250W, 100-240V |
| Power Consumption: HDD Sleep Mode | 24.14 |
| Power Consumption: Operating Mode, Typical | 37.32 |
| Fan | System: 1 x 12cm fan (12V DC)<br>CPU: 2 x 6cm blower fan |
| Sound Level | 28.1 |
| System Warning | Voice prompts or Buzzer |
| Kensington Security Slot | Yes |

Note: Use only QNAP memory modules to maintain system performance and stability. For NAS devices with more than one memory slot, use QNAP modules with identical specifications. Warning: Using unsupported modules may degrade performance, cause errors, or prevent the operating system from starting.
* Sound Level Test Environment: Refer to ISO 7779; Maximum HDD loaded; Bystander Position; Average data from 1 meter in front of operating NAS.
Designs and specifications are subject to change without notice.