



Lock Out Mode

Admin can lock all other user's permissions when switch on this mode



Random Digit

Remains the correct code continuous ,add code front or behind randomly, the maximum is 32 digit. e. g. XXX123456XXX

Correct Password

Random Digit

Specifications

Material	Zinc Alloy	
Mortise Type	American mortise (AL20B)	German mortise (AL20DB)
Door Thickness	30-54 mm (standard)	
User Capacity	100	
Password capacity	100	
Fingerprint capacity	100	
Wireless Module	BLE4.0	
Power Supply	4×AA Alkaline battery (NOT supplied)	
Dimensions	Front - 73(W)×179(L)×37(D)mm Back - 73(W)×179(L)×27(D)mm	




ZKBioBL APP Download For Android Platform



ZKBioBL APP Download For IOS Platform

Dimensions



80.0

90.0

©

41.0

| ⊕ 62.0

⊕₽

 \odot


German mortise


8


B 16.6

156.0

21.8







TESAN ILETISIM A.S.

E-mail: zkteco@tesan.com.tr Telefon: 0 (212) 454 60 00 © Copyright 2018. ZKTECO CO., LTD.ZKTeco Logo is a registered trademark of ZKTeco or a related company. All other product and company names mentioned are used for identification purposes only and may be the trademarks of their respective owners. All specifications are subject to change without notice. All rights reserved.

